CERTEX | Lifting Solutions Group
Axel Johnson International

Welded Master Link X-0080

Product information



- Welded Master Link designed for 1 leg chain, wire rope and webbing slings.
- At least 25% greater WLL than traditional Grade 8 products.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.

... *Read more*

Material: Quenched and Tempered Alloy Steel
Marking: According to standard, CE-mark, Type, manufacturer ID, traceability.
Temperature range: -40° up to +200°C (without reduction in WLL)
Finish: Blue Painted
Standard: EN 1677-4

Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Welded Master Link X-0080

Blueprint



Technical data

Part code	Code	Chain diameter mm	WLL ton	EWL mm	Proof Load kN	Used to single hook acc. to DIN 15401 No.	D mm	A mm	B mm	Weight kg
402100670540	ED-28	13	6.7	340	164	25	28	340	180	4.7
402101000540	ED-32	16	10	340	245	25	32	340	180	6.2
402101900540	ED-40	20-22	19	340	466	25	40	340	180	10

© November 2026 - All Rights Reserved