Lifting Solutions Group
Axel Johnson International

Pillar Jib Crane Articulated 350° PFSAM

Product information



Articulated pilar jib crane suspended with self-supporting hubs.

- Articulated pillar jib crane suspended for indoor use, 350° rotation for arm 1 and 300° rotation for arm 2
- This type of jib crane cannot be motorized
- Theoretical deflection under nominal load = approximately 1 / 250th of the span + height, without exceeding 1 / 100th of the span in itself
- The Maximum Moment (MM) is given as a rough guide and under nominal load
- Protection: polyester powder painting 60 microns C2
- Maximum hoisting speed = 16m/min

Options

- Lockable main switch
- Feeding line hoist
- Manual or electric hoist
- Chemical anchor kit
- Base plate for chemical anchors
- Hot dip galvanizing
- Covering for hoist

... *Read more*

Finish: RAL 1028 yellow

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Pillar Jib Crane Articulated 350° PFSAM

Technical data

I'd like to have more information

Pillar Jib Crane Articulated 350° PFSAM

Capacity / Span	2	3	4	5
50 kg	•	•	•	•
80 kg	•	•	•	•
125 kg	•	•	•	•
250 kg	•	•	•	
500 kg	•	•		
1000 kg	•			

© November 2026 - All Rights Reserved