

## Coil Hook without Counterweight CERTEX

### Product information

Coil hook without counterweight compensation for lifting and handling of coils and similar loads.

Coil hooks without counterweight compensation are crooked when unloaded, however, they have a very low dead weight. So the coil hook can easily be held in the scales by hand and be safely led into the coil eye.

**Design:** Lifting eye, handle, rounded tine.



| Part code       | WLL ton | AB mm | AH mm | BH mm | HM mm | IH mm | LSP mm | ZB mm | ZH mm | ZL mm | Weight kg | Delivery time |
|-----------------|---------|-------|-------|-------|-------|-------|--------|-------|-------|-------|-----------|---------------|
| 503500050000110 | 0.5     | 50    | 100   | 625   | 16    | 500   | 55     | 10    | 40    | 105   | 4         | 49            |
| 503500050000111 | 0.5     | 50    | 100   | 525   | 16    | 450   | 80     | 10    | 50    | 155   | 5         | 49            |
| 503500050000112 | 0.5     | 50    | 100   | 425   | 16    | 400   | 105    | 10    | 60    | 205   | 6         | 49            |
| 503500050000113 | 0.5     | 50    | 100   | 425   | 18    | 600   | 155    | 12    | 70    | 305   | 8         | 49            |
| 503500100000110 | 1       | 55    | 115   | 740   | 26    | 500   | 65     | 12    | 60    | 125   | 9         | 49            |
| 503500100000111 | 1       | 55    | 115   | 640   | 26    | 500   | 90     | 12    | 70    | 180   | 10        | 49            |
| 503500100000112 | 1       | 55    | 115   | 590   | 26    | 600   | 130    | 12    | 80    | 255   | 11        | 49            |
| 503500100000113 | 1       | 55    | 115   | 540   | 27    | 500   | 180    | 15    | 90    | 355   | 15        | 49            |
| 503500200000110 | 2       | 65    | 135   | 765   | 31    | 500   | 105    | 15    | 90    | 205   | 17        | 49            |
| 503500200000111 | 2       | 65    | 135   | 665   | 31    | 400   | 155    | 15    | 110   | 305   | 20        | 49            |
| 503500200000112 | 2       | 65    | 135   | 665   | 31    | 300   | 205    | 15    | 125   | 405   | 25        | 49            |
| 503500300000113 | 3       | 75    | 150   | 785   | 38    | 300   | 155    | 20    | 120   | 305   | 33        | 49            |
| 503500300000114 | 3       | 75    | 150   | 685   | 38    | 600   | 205    | 20    | 130   | 405   | 36        | 49            |
| 503500300000115 | 3       | 75    | 150   | 685   | 38    | 500   | 255    | 20    | 140   | 505   | 45        | 49            |

**Blueprint**

