

Clevis Grab Hook Pewag KPWP

Product information



KPWP Clevis grab hook is suitable for the shortening of chains and the forming of slings that must not tighten.

... [Read more](#)

Material: Alloy steel grade 12.

Marking: According to standard, CE-marked, Pewag or PW, winner pro or 12, H16, batch code and type.

Temperature range: -60°C up to +300°C.

Finish: Light blue powdercoated.

Standard: EN 1677-1


Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 12

Clevis Grab Hook Pewag KPWP

Blueprint



Technical data

| Part code | Code | WLL ton | e mm mm | b mm mm | dmm mm | g1mm mm | Weight kg |
|--------------|---------|---------|---------|---------|--------|---------|-----------|
| 403300230080 | KPWP 7 | 2.3 | 63 | 70 | 10 | 10 | 0.58 |
| 403300300080 | KPWP 8 | 3 | 62 | 70 | 11 | 10 | 0.58 |
| 403300500080 | KPWP 10 | 5 | 73 | 83 | 14 | 12 | 1 |
| 403300800080 | KPWP 13 | 8 | 98 | 104 | 18 | 16 | 2.29 |
| 403301250080 | KPWP 16 | 12.5 | 124 | 123 | 21 | 19 | 4.32 |