



## Wire Rope Lifting Sling WLS-002

### Product information

**Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm<sup>2</sup>\***

(\*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm<sup>2</sup>)

**Design:** Endless with master link and mechanical aluminium spliced thimbles.

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope constructions possible on request. In that case, please contact us to discuss the possible options or specify it with your request.

**Note:** We recommend that the sling not is bent over a diameter less than 6 times the wire rope diameter without reducing the WLL.

Part code	Diameter mm	WLL ton	Delivery time
1601	3	0.23	30
1601	4	0.42	30
1601	5	0.65	30
1601	6	0.94	30
1601	7	1.28	30
1601	8	1.64	30
1601	9	2.07	30
1601	10	2.56	30

1601	11	3.1	30
1601	12	3.67	30
1601	13	4.33	30
1601	14	5.03	30
1601	16	6.57	30
1601	18	8.3	30
1601	20	10.24	30
1601	22	12.41	30
1601	28	16.8	30
1601	26	17.33	30
1601	24	17.46	30
1601	32	20.08	30
1601	36	26.25	30
1601	40	33.19	30
1601	44	41.11	30
1601	48	49.56	30
1601	52	59.1	30
1601	56	69.38	30

## Technical data