



Digital load indicator with remote reading 3-10 t

Product information

The crane scale/load indicator can be used as a normal crane scale or, for example, to measure pulling forces. Equipped with an illuminated LCD display. Operating time with rechargeable 3×AA NiMH batteries approx. 30 hours. Includes charger.

Wireless remote reader has a range of 50-70 m (unobstructed visibility). The weight of the load is updated in real time on the screen. It displays the battery charge level of remote and the load indicator's battery. Equipped with a rechargeable battery. Supplied with charging cable (USB-C)

Remote reader functions: display backlight, tare, peak, hold, unit change, automatic shutdown, battery charge indicator, signal strength, time/date, password to start.

Material: Aluminium

Marking: CE-marked

Temperature range: -10-(+)40°C

Note: Shackles included in delivery

Safety factor: 4:1

Part code	WLL ton	Resolution kg	A,	B,	C,	D,	E,	F,	Weight kg	Delivery time
6097KV3KIE	3	1	360	95	91	67	59	50	3.4	3
6097KV5KIE	5	2	400	95	91	67	73	53	5.6	3
6097KV10KIE	10	5	560	95	91	67	123	90	13	3

Technical data

SPARE PARTS

Spare part (product code)	Description	Suitable for (product code)
KVKIELAT	Battery charger	KV3KIE, KV5KIE, KV10KIE
KVKIEKAUKO	Wireless indicator / remote control	KV3KIE, KV5KIE, KV10KIE

Blueprint

