

## **Verolube Spray**

## **Product information**

Verolube Spray is used for lubrication and is a very fluid rope lubricant. It penetrates well into the cable strands and provides corrosion protection, wear protection, water resistance, weather resistance and adhesion.

The wire rope lubricant has two major tasks: it should protect the rope from corrosion and it should minimize the friction between the rope elements themselves and between the rope and the sheave or the drum. A reduction of the friction reduces the actuating power and minimizes the wear of the rope, the sheaves and the drums. We differentiate between wax-based lubricants and oil-based lubricants. While wax-based lubricants offer a better handling of the ropes, the oil-based lubricants advantage is a better closing of the lubrication film due to the gravitational force of the oil. The quality of the wire rope lubricant has a great impact on the fatigue resistance of a wire rope

Packaging: Spray can 600 ml.

Colour: Black
Due to oil: Min
Fixed lubricants: C

Temperature range: -35 up to +65°

Part code	Designation	Value	DIN/Regulation	Delivery time
142540000102	Colour	Black	LLS 134	30
1425	Service temperature range	-35/+65°	-	30
1425	Due to oil	Min	-	30
1425	Fixed lubricants	С	-	30

## **Technical data**

Designation	Value	
Colour	Black	
Service temperature range	- 35/+65°	
Due to oil	Min	
Fixed lubricants	С	