

Work Positioning and Restraint Lanyard Powertex WPL/RL

Product information



The Powertex Work Positioning & Restraint Lanyard WPL/RL is a versatile rope lanyard designed to support work positioning and fall restraint tasks at height. It keeps the user stable and correctly positioned while reducing unnecessary movement into fall hazard zones. Built from 11 mm polyamide rope with aluminium hardware and a one-hand adjuster, it offers secure adjustment and reliable performance

When to choose this product:

- When you need to position workers hands-free at height for precision tasks
- To limit worker movement into fall danger zones, reducing reliance on full fall arrest systems
- On scaffolding, towers, structures, trees or maintenance sites where controlled positioning is required

Product benefits

- **Supports stable and comfortable work positioning**
The 11 mm polyamide kernmantle rope offers a good balance of flexibility and strength, enabling users to maintain a secure working position with reduced fatigue.
- **One-hand adjustment for precise positioning**
The aluminum adjuster allows for quick length changes with one hand, making fine adjustments easy, even during active work.
- **Lightweight aluminium hardware reduces handling effort**
The double-action hook and triple-action karabiner provide secure connections while maintaining a low overall weight for daily use.
- **Supports users up to 140 kg, including tools and equipment**
Tested and certified for a maximum user weight of 140 kg, allowing safe use by a wider range of workers together with their carried tools and equipment. [... Read more](#)

Marking: According to standard, CE-marked, Supplier symbol, Product identification, Max weight, Length (max), Production date, Serial number

Temperature range: -25°C up to +50°C

Standard: EN 358

Work Positioning and Restraint Lanyard Powertex WPL/RL

Technical data

Part code	Max. number of persons	Length m	Max. rated load kg	Weight kg
821100204130	1	2	140	0.5
821100304130	1	3	140	0.6
821100504130	1	5	140	0.8
821101004130	1	10	140	1.2