

## Lifting Beam Type LO

### Product information



### CERTEX

This type of lifting beam functions primarily as a spreader beam meaning that a 2-part sling must be used between the crane hook and the lifting beam. The lifting beam is designed with 2x3 attachment points, which makes it possible to have several different types of attachments mounted on the lifting beam at the same time. Other lengths and working loads can be manufactured upon request.

**Design:** Lightweight welded pipe beam construction providing good torsional stiffness.

**Proof load:** Usually 1,5 x WLL.

[... Read more](#)


**Marking:** Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

**Finish:** Yellow painted. Other treatments available on request.

**Note:** Top sling, separate slings and other accessories to be ordered separately.

## Lifting Beam Type LO

### Blueprint



### Technical data

Part code	Code	WLL 90° ton	WLL 120° ton	B mm	L mm	L min. mm mm	L max. mm mm	Weight kg
6205630051500	LO-0,5/1,5	0.5	0.3	50	1,500	1,300	1,700	12
6205630052000	LO-0,5/2	0.5	0.3	50	2,000	1,800	2,200	14
6205630052500	LO-0,5/2,5	0.5	0.3	50	2,500	2,300	2,700	16
6205630053000	LO-0,5/3	0.5	0.3	50	3,000	2,800	3,200	19
6205630101500	LO-1/1,5	1	0.7	70	1,500	1,300	1,700	20
6205630053500	LO-0,5/3,5	0.5	0.3	50	3,500	3,300	3,700	21
6205630102000	LO-1/2	1	0.7	70	2,000	1,800	2,200	24
6205630102500	LO-1/2,5	1	0.7	70	2,500	2,300	2,700	28
6205630201500	LO-2/1,5	2	1.2	90	1,500	1,300	1,700	31
6205630103000	LO-1/3	1	0.7	70	3,000	2,800	3,200	32
6205630103500	LO-1/3,5	1	0.7	70	3,500	3,300	3,700	36
6205630202000	LO-2/2	2	1.2	90	2,000	1,800	2,200	37
6205630054000	LO-0,5/4	0.5	0.3	70	4,000	3,800	4,200	40
6205630202500	LO-2/2,5	2	1.2	90	2,500	2,300	2,700	43
6205630055000	LO-0,5/5	0.5	0.3	70	5,000	4,800	5,200	48
6205630203000	LO-2/3	2	1.2	90	3,000	2,800	3,200	49
6205630302000	LO-3/2	3	2	120	2,000	1,800	2,200	52
6205630203500	LO-2/3,5	2	1.2	90	3,500	3,300	3,700	55
6205630056000	LO-0,5/6	0.5	0.3	70	6,000	5,800	6,200	56
6205630104000	LO-1/4	1	0.7	90	4,000	3,800	4,200	61
6205630502000	LO-5/2	5	3	120	2,000	1,800	2,200	68
6205630303000	LO-3/3	3	2	120	3,000	2,800	3,200	69

## Lifting Beam Type LO

### Technical data

Part code	Code	WLL 90° ton	WLL 120° ton	B mm	L mm	L min. mm mm	L max. mm mm	Weight kg
6205630105000	LO-1/5	1	0.7	90	5,000	4,800	5,200	73
6205630802000	LO-8/2	8	5	140	2,000	1,800	2,200	83
6205630106000	LO-1/6	1	0.7	90	6,000	5,800	6,200	85
6205630204000	LO-2/4	2	1.2	90	4,000	3,800	4,200	87
6205630304000	LO-3/4	3	2	120	4,000	3,800	4,200	87
6205630503000	LO-5/3	5	3	120	3,000	2,800	3,200	89
6205631002000	LO-10/2	10	6	140	2,000	1,800	2,200	99
6205630205000	LO-2/5	2	1.2	100	5,000	4,800	5,200	105
6205630803000	LO-8/3	8	5	140	3,000	2,800	3,200	105
6205630504000	LO-5/4	5	3	120	4,000	3,800	4,200	110
6205630206000	LO-2/6	2	1.2	100	6,000	5,800	6,200	123
6205631003000	LO-10/3	10	6	150	3,000	2,800	3,200	123
6205630804000	LO-8/4	8	5	140	4,000	3,800	4,200	128
6205630305000	LO-3/5	3	2	140	5,000	4,800	5,200	131
6205631004000	LO-10/4	10	6	150	4,000	3,800	4,200	147
6205630505000	LO-5/5	5	3	120	5,000	4,800	5,200	151
6205630306000	LO-3/6	3	2	140	6,000	5,800	6,200	152
6205630805000	LO-8/5	8	5	140	5,000	4,800	5,200	171
6205630506000	LO-5/6	5	3	120	6,000	5,800	6,200	173
6205630806000	LO-8/6	8	5	140	6,000	5,800	6,200	195
6205631604000	LO-16/4	16	10	200	4,000	3,800	4,200	205
6205631005000	LO-10/5	10	6	150	5,000	4,800	5,200	206
6205631605000	LO-16/5	16	10	200	5,000	4,800	5,200	226
6205631006000	LO-10/6	10	6	150	6,000	5,800	6,200	233
6205631606000	LO-16/6	16	10	200	6,000	5,800	6,200	256