Lifting Solutions Group
Axel Johnson International

Lifting Beam Type H

Product information



This type of lifting beam cannot be adjusted and is designed for direct attachment with the crane hook in the central lifting eye. The lifting beam is designed with one attachment point in each corner and is based on lifting assignments in all four points. Other lengths and working loads can be manufactured upon request.
Design: Lightweight welded pipe beam construction providing good torsional stiffness.
Test load: 1.5 x WLL

... *Read more*


Material: Hollow beam and plate manufactured with high-strength structural steel.
Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.
Finish: Yellow painted. Other treatments available on request.
Note: Top sling, separate slings and other accessories to be ordered separately.

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Lifting Beam Type H

Blueprint



Technical data

Part code	Code	WLL	H mm	L1 mm	L2 mm	Weight kg
62056410051500	H-0,5/2-1,5	0.5	255	2,000	1,500	80
62056410052000	H-0,5/3-2	0.5	255	3,000	2,000	109
62056410052500	H-0,5/4-2,5	0.5	255	4,000	2,500	152
62056410151500	H-1,5/2-1,5	1.5	310	2,000	1,500	102
62056410152000	H-1,5/3-2	1.5	310	3,000	2,000	139
62056410152500	H-1,5/4-2,5	1.5	310	4,000	2,500	216
62056410301500	H-3/2-1,5	3	395	2,000	1,500	131
62056410302000	H-3/3-2	3	395	3,000	2,000	185
62056410302500	H-3/4-2,5	3	395	4,000	2,500	263
62056410501500	H-5/2-1,5	5	440	2,000	1,500	193
62056410502000	H-5/3-2	5	440	3,000	2,000	275
62056410502500	H-5/4-2,5	5	440	4,000	2,500	388
62056410801500	H-8/2-1,5	8	555	2,000	1,500	326
62056410802000	H-8/3-2	8	555	3,000	2,000	422
62056410802500	H-8/4-2,5	8	555	4,000	2,500	565
62056411001500	H-10/2-1,5	10	720	2,000	1,500	502
62056411002000	H-10/3-2	10	720	3,000	2,000	647
62056411002500	H-10/4-2,5	10	720	4,000	2,500	793

© November 2026 - All Rights Reserved