

Lifting Beam Type H-SB

Product information



CERTEX

This type of lifting beam has adjustable attachment points in one direction via a cam beam and is based on lifting in four points. The lifting beam is designed for direct attachment with the crane hook in the central lifting eye. The attachment points are designed as oval rings, which makes it possible to use for example a 2-part sling. Other lengths and working loads can be manufactured upon request.

Design: Lightweight welded beam construction providing good torsional stiffness.

Proof load: Usualley 1,5 x WLL.

Material: Beam and plate of high-strength structural steel.

Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Note: Top sling, separate slings and other accessories to be ordered separately.

Part code	Code	WLL ton	H mm	L1 mm	L2 mm	Weight kg	Delivery time
62056420051500	H-SB-0,5/2-1,5	0.5	280	2,000	1,500	97	30
62056420052000	H-SB-0,5/3-2	0.5	280	3,000	2,000	143	30
62056420052500	H-SB-0,5/4-2,5	0.5	280	4,000	2,500	173	30
62056420151500	H-SB-1,5/2-1,5	1.5	330	2,000	1,500	135	30
62056420152000	H-SB-1,5/3-2	1.5	330	3,000	2,000	178	30
62056420152500	H-SB-1,5/4-2,5	1.5	330	4,000	2,500	256	30
62056420301500	H-SB-3/2-1,5	3	415	2,000	1,500	165	30
62056420302000	H-SB-3/3-2	3	415	3,000	2,000	224	30
62056420302500	H-SB-3/4-2,5	3	415	4,000	2,500	302	30
62056420501500	H-SB-5/2-1,5	5	455	2,000	1,500	229	30
62056420502000	H-SB-5/3-2	5	455	3,000	2,000	320	30
62056420502500	H-SB-5/4-2,5	5	455	4,000	2,500	428	30
62056420801500	H-SB-8/2-1,5	8	595	2,000	1,500	422	30
62056420802000	H-SB-8/3-2	8	595	3,000	2,000	524	30
62056420802500	H-SB-8/4-2,5	8	595	4,000	2,500	667	30
62056421001500	H-SB10/2-1,5	10	760	2,000	1,500	609	30
62056421002000	H-SB-10/3-2	10	760	3,000	2,000	760	30
62056421002500	H-SB10/4-2,5	10	760	4,000	2,500	906	30

Blueprint

