Lifting Solutions Group
Axel Johnson International

Beam Clamp IPTKU

Product information



The Crosby IPTKU series beam clamp has an improved hinged hoisting eye that increases the loading angles and WLL range from 2 to 10 tonnes.

Best used for:

- Transferring steel beams in industrial lifting and material handling operations.
- Applications requiring specific hoisting eye configurations and jaw openings matched to the load.

Product benefits:

- Welded alloy steel body provides strength with compact dimensions.
- Jaw openings from 75 to 460 mm accommodate different beam dimensions.
- Individually proof tested to twice the WLL, with certification supplied.
- Permanent WLL identification and individual serial numbers support inspection and traceability.
- Supplied with documentation; available maintenance and repair kits support servicing.

... *Read more*

Material: Alloy steel.
Marking: According to standard, CE-mark, WLL, Logo, Type, Jaw opening, Serial number, Proof load test date
Temperature range: -40°C (-40°F) up to +100°C (+212°F)
Standard: EN 13155

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Beam Clamp IPTKU

Blueprint



Technical data

Part code	WLL ton	Jaw width mm	Model	Jaw A mm	C mm	D mm	E mm	H mm	J mm	K mm	Weight kg
502300201900020	2	75-190	2-IPTKU	75-190	A + 100	121	76	22	99	19	5.7
502300301900020	3	75-190	3-IPTKU	75-190	A + 100	121	89	22	122	22	6.4
502300402800020	4	120-180	4-IPTKU	120-180	A + 150	140	89	40	122	22	12.1
502300503500020	5	120-350	5-IPTKU	120-350	A + 175	140	89	40	122	22	14.5
502301004600020	10	200-460	10-IPTKU	200-460	A + 300	200	105	60	152	26	41

© November 2026 - All Rights Reserved