

Beam Clamp - IPTKW

Product information



The IPTKW series beam clamp is suitable for use as a temporary tackle eye for a beam and it is an economy version of the IPTK model.

Features:

- Available in capacities of 2 thru 5 metric tons.
- Wide variety of jaw openings available: 75 to 350 mm.
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available.
- All sizes are RFID EQUIPPED.

Material: Alloy steel

Marking: According to standard, CE-marked, WLL, Logo, Jaw opening, Serial number

Temperature range: -40°C up to +100°C

Standard: EN 13155

| Part code | WLL ton | Jaw width mm | Model | A mm | C mm | D mm | F mm | H mm | Weight kg | Delivery time |
|-----------------|---------|--------------|---------|---------|-------|------|------|------|-----------|---------------|
| 502100201900220 | 2 | 75-190 | 2-IPTKW | 75-190 | A+80 | 125 | 28 | 25 | 4 | 30 |
| 502100301900220 | 3 | 75-190 | 3-IPTKW | 75-190 | A+80 | 125 | 28 | 25 | 4.5 | 30 |
| 502100402800220 | 4 | 150-280 | 4-IPTKW | 150-280 | A+100 | 125 | 33 | 35 | 6.3 | 30 |
| 502100503500220 | 5 | 120-350 | 5-IPTKW | 120-350 | A+195 | 125 | 33 | 40 | 8.8 | 30 |

Blueprint

