CERTEX | Lifting Solutions Group
Axel Johnson International

# Anchor Clamp IPTKUM

**Product information**



This anchor clamp is suitable as an anchor device for one person, for the attachment of components forming part of a personal protection system.
The steel beams must have a flange width of minimum 75 mm up to maximum 190 mm and a flange thickness of minimum 5 mm and maximum 22 mm.

**Features:**

- Easy to operate (ergonomic).
- Low own weight.
- Double locking system.
- Spindle with hexagon head for fast pneumatical or electronic opening and closing.
- Supplied with certificate and manual.
- Frame is galvanized (sherardised).

... *Read more*


**Material:** Alloy steel.
**Marking:** According to standard, CE-mark
**Finish:** Galvanized
**Standard:** EN 795

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Anchor Clamp IPTKUM

## Blueprint




## Technical data

| Part code | Max. number of persons | Model | Max. number of persons | Jaw width mm mm | C mm | D mm | E mm | H mm | J mm | K mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 84152709991 | 1 | IPTKUM | 1 | 75-190 | jaw+100 | 165 | 76 | 22 | 99 | 19 | 6 |

© November 2026 - All Rights Reserved