Lifting Solutions Group
Axel Johnson International

Snatch Block McKissick 418 with Hook - Light Champion

Product information



The McKissick snatch block 418 Light Champion from Crosby is a snatch block fitted with a hook. Available from WLL 2 up to 15 T.
Can be delivered with bronze bushing (BB) and from WLL 8 T also with roller bearing (RB).

Features:

- Bolt for opening feature is retained, to ensure no lost bolts.
- Opening feature permits easy insertion of rope without reeving, or while the block is suspended.
- Center pin equipped with pressure lube fitting.
- All sizes feature sheave grooves suited for a range of wire line diameters.
- Meets or exceeds all requirements of ASME B30.26 including identification ductility, design factor, proof load and temperature requirements.
- Meet other critical performance requirements including fatigue life and material traceability, not addressed by ASME B30.26.

... *Read more*

Material: Forged steel.
Marking: CE-mark


Safety factor: 4:1

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Snatch Block McKissick 418 with Hook - Light Champion

Blueprint



Technical data

Part code	Code	Rope Ø range mm	WLL ton	Sheave dia mm	Bearing	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Weight kg
424100200230	418	8-10	2	76	BB	247	47	67	91	19	164	19	25	2.3
424100400230	418	10-13	4	114	BB	359	108	79	133	25	257	24	47	5.4
424100800230	418	16-19	8	152	BB	481	152	106	173	40	344	33	61	12.2
424100800235	418	16-19	8	152	RB	481	152	106	173	40	344	33	61	12.2
424100800236	418	16-19	8	203	BB	534	206	106	173	40	369	33	61	15
424100800237	418	16-19	8	203	RB	534	206	106	173	40	369	33	61	15
424100800238	418	16-19	8	254	BB	586	257	106	173	40	396	33	61	18.6
424100800239	418	16-19	8	254	RB	586	257	106	173	40	396	33	61	18.6
4241008002310	418	16-19	8	305	BB	658	308	106	173	40	442	33	61	21.8
4241008002311	418	16-19	8	305	RB	658	308	106	173	40	442	33	61	21.8
4241008002312	418	16-19	8	356	BB	696	359	106	173	40	455	33	61	24.9
4241008002313	418	16-19	8	356	RB	696	359	106	173	40	455	33	61	24.9
424101500230	418	19-22	15	406	BB	819	409	129	212	45	540	37	74	59
424101500235	418	19-22	15	406	RB	851	460	129	212	45	546	38	74	59
424101500236	418	22-26	15	457	BB	851	460	129	212	45	546	38	74	68
424101500237	418	22-26	15	457	RB	851	460	129	212	45	546	38	74	68

© November 2026 - All Rights Reserved