

## Chain SA/S - EN818-2 Gr. 10

### Product information



**General:** Chain for lifting or lashing (other safety factor). Available in 2 different qualities

#### Star Alloy (SA/S)

- Working temperature: max. 200°C
- Grade Marking: "10" on link every 300mm (up to 16mm) others every 900 mm.
- Surface: Purple varnished

**Star Alloy Plus+ (SAP/S):** for working temperatures up to 380°C (Available on request)

**Material:** Alloy steel.

**Marking:** According to standard

**Temperature range:** Star Alloy SA/S: -40°C up to 200°C - Star Alloy Plus+ SAP/S: -40°C up to 380°C

**Standard:** EN 818-2

*higher capacity*

**Warning:** Not to be heat treated.

**Safety factor:** 4:1

**Grade:** 10

Part code	Chain diameter mm	WLL ton	Min. breaking force kN	Pitch Length	D, mm	Pmm mm	Li min. mm	Le max. mm	Weight kg/m	Delivery time
203500600000050	6	1.4	56.5	18	6	18	8.7	22	0.96	30
203500700000050	7	1.9	77	21	7	21	9.5	25	1.2	3
203500800000050	8	2.5	101	24	8	24	10.9	29	1.57	30
203501000000050	10	4	157	30	10	30	13.5	36	2.46	3
203501300000050	13	6.7	265	39	13	39	17.5	47	4.18	3
203501600000050	16	10	402	48	16	48	21.5	58	6.28	3
203501900000050	19	14	567	57	19	57	26.6	69	8.9	3
203502200000050	22	19	760	66	22	66	29.5	79	11.88	30
203502600000050	26	26.5	1,060	78	26	78	35	94	16.18	30

## Blueprint

