



## Load Hook HKS/S Grade 10 - Clevis/Latch

### Product information

Clevis Load hook - Sling hook with safety latch for general lifting applications.

**Material:** Alloy steel.

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to 380°C

**Finish:** Violet powder coated.

**Standard:** EN 1677-2

(+ 25% WLL)

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

Part code	Code	WLL ton	EWL mm	For chain Ø mm	a mm	b mm	d mm	e mm	g mm	h mm	Weight kg	Delivery time
402300140430	HKS/S-6	1.4	69	6	15	66	7	69	19	20	0.25	3
402300190430	HKS/S-7	1.9	95	7	19	90	9	95	26	28	0.68	3
402300250430	HKS/S-8	2.5	95	8	19	90	10	95	26	28	0.58	3
402300400430	HKS/S-10	4	109	10	25	108	12.5	109	31	35	1.14	30
402300670430	HKS/S-13	6.7	136	13	34	131	16	136	39	41	2.02	3
402301000430	HKS/S-16	10	155	16	37	153	20	155	45	49	3.57	3
402301600430	HKS/S-19/20	16	184	19-20	51	177	24	184	53	53	5.55	30
402301900430	HKS/S-22	19	214	22	52	196	27	214	62	62	8.99	30

Blueprint

