



## Connecting Link V/S Grade 10

### Product information

Connecting link for: masterlink - chain, chain - chain, (eye)hook - chain.

**Material:** Alloy steel.

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to 380°C

**Finish:** Violet powder coated.

**Standard:** EN 1677-1 (+ 25% WLL)

**Note:** Not to be heat-treated.

**Warning:** For straight in-line pull only. Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 10

Part code	Code	WLL ton	For chain Ø mm	B,	C,	D,	E,	G,	S mm	Weight kg	Delivery time
402200140100	V/S 6	1.4	6	39	8	8	44	14	11	0.11	3
402200190100	V/S 7	1.9	7	47	10	9	51	17	13	0.2	3
402200250100	V/S 8	2.5	8	55	12	10	62	18	14	0.29	3
402200400100	V/S 10	4	10	64	15	13	72	24	18	0.52	3
402200670100	V/S 13	6.7	13	79	20	17	88	28	22	0.91	3
402201000100	V/S 16	10	16	106	21	21	103	33	29	1.34	3
402201600100	V/S 19/20	16	19-20	123	30	24	115	42	35	3.33	30
402201900100	V/S 22	19	22	148	34	25	161	51	39	3.14	3
402202650100	V/S 26	26.5	26	175	40	30	190	60	46	5.72	30

## Blueprint

