

Stainless steel sling 2-leg RCM-RCL-RCB

Product information





Rema®'s Grade 6 Stainless Steel Chain Slings are meticulously crafted using top-tier stainless steel (AISI 316), our slings are not just durable but also versatile. With the availability of individual components, we ensure a sustainable and customizable solution tailored to your specific lifting requirements. Our stainless steel assemblies are trusted across a myriad of industries such as construction, food & beverage, healthcare, aerospace, marine, and beyond.

Utilization Features:

- 1. Durability: Made with premium AISI 316 stainless steel, ensuring longevity and resistance to corrosion.
- 2. Versatility: Suitable for a range of lifting operations with various assembly options.
- 3. Safety: Comes with a CE-mark and a safety factor of 4, ensuring utmost safety during operations.
- 4. Adaptability: Individual component availability for a tailored lifting solution.

Markets/Applications:

- Construction: Ideal for heavy-duty lifting and construction site operations.
- Food & Beverage: Stainless steel ensures hygiene and cleanliness, making it perfect for food-related lifting tasks.
- Medical: Suitable for lifting medical equipment and supplies.
- Aerospace: Can be used for lifting aerospace components.
- Marine: Resistant to corrosion, making it perfect for marine applications.

Link to components

• 2 x RC stainless steel chain | masterlink RCM | 2 x connecting link RCL | 2 x clevis sling hook RCB | AISI 316 TAG

Marking: CE-marked

Safety factor: 4 Grade: 6

| Part code | GTIN No. | Chain diameter mm | WLL ton | WLL Straight Lift ton | WLL 0-45° t | WLL 45-60° t | Length | Model | Weight kg | Delivery time |
|--------------|---------------|----------------------|------------|--------------------------|----------------|-----------------|--------|-------------------------|--------------|---------------|
| R2689206-1 | 8717365185106 | 6 | 1.26 | 1.26 | 1.26 | 0,900 | 1 | 1.26T-6MM-RCM-RCB-1M | 2.6 | 3 |
| R2689206-1,5 | 8717365185113 | 6 | 1.26 | 1.26 | 1.26 | 0,900 | 1.5 | 1.26T-6MM-RCM-RCB-1.5M | 3.18 | 3 |
| R2689206-2 | 8717365185120 | 6 | 1.26 | 1.26 | 1.26 | 0,900 | 2 | 1.26T-6MM-RCM-RCB-2M | 3.76 | 3 |
| R2689207-1 | 8717365185137 | 7 | 1.75 | 1.75 | 1.75 | 1,250 | 1 | 1.75T-7MM-RCM-RCB-1M | 4.64 | 3 |
| R2689207-1,5 | 8717365185144 | 7 | 1.75 | 1.75 | 1.75 | 1,250 | 1.5 | 1.75T-7MM-RCM-RCB-1.5M | 5.75 | 3 |
| R2689207-2 | 8717365185151 | 7 | 1.75 | 1.75 | 1.75 | 1,250 | 2 | 1.75T-7MM-RCM-RCB-2M | 6.86 | 3 |
| R2689208-1 | 8717365185168 | 8 | 2.24 | 2.24 | 2.24 | 1,600 | 1 | 2.24T-8MM-RCM-RCB-1M | 6.05 | 3 |
| R2689208-1,5 | 8717365185175 | 8 | 2.24 | 2.24 | 2.24 | 1,600 | 1.5 | 2.24T-8MM-RCM-RCB-1.5M | 7.73 | 3 |
| R2689208-2 | 8717365185182 | 8 | 2.24 | 2.24 | 2.24 | 1,600 | 2 | 2.24T-8MM-RCM-RCB-2M | 9.41 | 3 |
| R2689210-1 | 8717365185199 | 10 | 3.5 | 3.5 | 3.5 | 2,500 | 1 | 3.5T-10MM-RCM-RCB-1M | 12.28 | 3 |
| R2689210-1,5 | 8717365185205 | 10 | 3.5 | 3.5 | 3.5 | 2,500 | 1.5 | 3.5T-10MM-RCM-RCB-1.5M | 16.05 | 3 |
| R2689210-2 | 8717365185212 | 10 | 3.5 | 3.5 | 3.5 | 2,500 | 2 | 3.5T-10MM-RCM-RCB-1M | 19.82 | 3 |
| R2689213-1 | 8717365185229 | 13 | 5.95 | 5.95 | 5.95 | 4,250 | 1 | 5.95T-13MM-RCM-RCA-1M | 21.18 | 3 |
| R2689213-1,5 | 8717365185236 | 13 | 5.95 | 5.95 | 5.95 | 4,250 | 1.5 | 5.95T-13MM-RCM-RCA-1.5M | 26.8 | 3 |
| R2689213-2 | 8717365185243 | 13 | 5.95 | 5.95 | 5.95 | 4,250 | 2 | 5.95T-13MM-RCM-RCA-2M | 32.42 | 3 |