

Stainless steel sling 2-leg RCM-RCL-RCB

Product information





Rema®'s Grade 6 Stainless Steel Chain Slings are meticulously crafted using top-tier stainless steel (AISI 316), our slings are not just durable but also versatile. With the availability of individual components, we ensure a sustainable and customizable solution tailored to your specific lifting requirements. Our stainless steel assemblies are trusted across a myriad of industries such as construction, food & beverage, healthcare, aerospace, marine, and beyond.

Utilization Features:

- 1. Durability: Made with premium AISI 316 stainless steel, ensuring longevity and resistance to corrosion.
- 2. Versatility: Suitable for a range of lifting operations with various assembly options.
- 3. Safety: Comes with a CE-mark and a safety factor of 4, ensuring utmost safety during operations.
- 4. Adaptability: Individual component availability for a tailored lifting solution.

Markets/Applications:

- Construction: Ideal for heavy-duty lifting and construction site operations.
- Food & Beverage: Stainless steel ensures hygiene and cleanliness, making it perfect for food-related lifting tasks.
- Medical: Suitable for lifting medical equipment and supplies.
- Aerospace: Can be used for lifting aerospace components.
- Marine: Resistant to corrosion, making it perfect for marine applications.

Link to components

• 2 x RC stainless steel chain | masterlink RCM | 2 x connecting link RCL | 2 x clevis sling hook RCB | AISI 316 TAG

Marking: CE-marked

Safety factor: 4 Grade: 6

| Part code | WLL ton |
|--------------|------------|
| R2689206-1 | 1.26 |
| R2689206-1,5 | 1.26 |
| R2689206-2 | 1.26 |
| R2689207-1 | 1.75 |
| R2689207-1,5 | 1.75 |
| R2689207-2 | 1.75 |
| R2689208-1 | 2.24 |
| R2689208-1,5 | 2.24 |
| R2689208-2 | 2.24 |
| R2689210-1 | 3.5 |
| R2689210-1,5 | 3.5 |
| R2689210-2 | 3.5 |
| R2689213-1 | 5.95 |
| R2689213-1,5 | 5.95 |
| R2689213-2 | 5.95 |