

## Stainless steel sling 3-leg RCMC-RCL-RCB

### Product information



Rema®'s Grade 6 Stainless Steel Chain Slings are meticulously crafted using top-tier stainless steel (AISI 316), our slings are not just durable but also versatile. With the availability of individual components, we ensure a sustainable and customizable solution tailored to your specific lifting requirements. Our stainless steel assemblies are trusted across a myriad of industries such as construction, food & beverage, healthcare, aerospace, marine, and beyond.

#### Utilization Features:

1. **Durability:** Made with premium AISI 316 stainless steel, ensuring longevity and resistance to corrosion.
2. **Versatility:** Suitable for a range of lifting operations with various assembly options.
3. **Safety:** Comes with a CE-mark and a safety factor of 4, ensuring utmost safety during operations.
4. **Adaptability:** Individual component availability for a tailored lifting solution.

#### Markets/Applications:

- **Construction:** Ideal for heavy-duty lifting and construction site operations.
- **Food & Beverage:** Stainless steel ensures hygiene and cleanliness, making it perfect for food-related lifting tasks.
- **Medical:** Suitable for lifting medical equipment and supplies.
- **Aerospace:** Can be used for lifting aerospace components.
- **Marine:** Resistant to corrosion, making it perfect for marine applications.

#### Link to components

- 3 x RC stainless steel chain | masterlink RCMC | 3 x connecting link RCL | 3 x hook RCB [... Read more](#)

**Marking:** CE-marked

**Safety factor:** 4

**Grade:** 6

## Stainless steel sling 3-leg RCMC-RCL-RCB

### Technical data

Part code	GTIN No.	Chain diameter mm	WLL ton	WLL 45-60° t	Length	Model	Weight kg
R2689306-1	8717365185250	6	1.89	1,350	1	1.89T-6MM-RCMC-RCB-1M	3.81
R2689306-1.5	8717365185267	6	1.89	1,350	1.5	1.89T-6MM-RCMC-RCB-1.5M	4.68
R2689306-2	8717365185274	6	1.89	1,350	2	1.89T-6MM-RCMC-RCB-2M	5.55
R2689307-1	8717365185281	7	2.625	1,875	1	2.625T-7MM-RCMC-RCB-1M	7.32
R2689307-1.5	8717365185298	7	2.625	1,875	1.5	2.625T-7MM-RCMC-RCB-1.5M	8.99
R2689307-2	8717365185304	7	2.625	1,875	2	2.625T-7MM-RCMC-RCB-2M	10.65
R2689308-1	8717365185311	8	3.36	2,400	1	3.36T-8MM-RCMC-RCB-1M	9.78
R2689308-1.5	8717365185328	8	3.36	2,400	1.5	3.36T-8MM-RCMC-RCB-1.5M	12.3
R2689308-2	8717365185335	8	3.36	2,400	2	3.36T-8MM-RCMC-RCB-2M	14.82
R2689310-1	8717365185342	10	5.25	3,750	1	3.5T-10MM-RCMC-RCB-1M	19.88
R2689310-1.5	8717365185359	10	5.25	3,750	1.5	3.5T-10MM-RCMC-RCB-1.5M	25.54
R2689310-2	8717365185366	10	5.25	3,750	2	3.5T-10MM-RCMC-RCB-1M	31.19
R2689313-1	8717365185373	13	8.925	6,375	1	5.95T-13MM-RCMC-RCA-1M	33.87
R2689313-1.5	8717365185380	13	8.925	6,375	1.5	5.95T-13MM-RCMC-RCA-1.5M	42.3
R2689313-2	8717365185397	13	8.925	6,375	2	5.95T-13MM-RCMC-RCA-2M	50.73