



Stainless steel sling 4-leg RCMC-RCL-RCB

Product information

Rema®'s Grade 6 Stainless Steel Chain Slings are meticulously crafted using top-tier stainless steel (AISI 316), our slings are not just durable but also versatile. With the availability of individual components, we ensure a sustainable and customizable solution tailored to your specific lifting requirements. Our stainless steel assemblies are trusted across a myriad of industries such as construction, food & beverage, healthcare, aerospace, marine, and beyond.

Utilization Features:

1. **Durability:** Made with premium AISI 316 stainless steel, ensuring longevity and resistance to corrosion.
2. **Versatility:** Suitable for a range of lifting operations with various assembly options.
3. **Safety:** Comes with a CE-mark and a safety factor of 4, ensuring utmost safety during operations.
4. **Adaptability:** Individual component availability for a tailored lifting solution.

Markets/Applications:

- **Construction:** Ideal for heavy-duty lifting and construction site operations.
- **Food & Beverage:** Stainless steel ensures hygiene and cleanliness, making it perfect for food-related lifting tasks.
- **Medical:** Suitable for lifting medical equipment and supplies.
- **Aerospace:** Can be used for lifting aerospace components.
- **Marine:** Resistant to corrosion, making it perfect for marine applications.

Link to components

- 4 x RC stainless steel chain | masterlink RCMC | 4 x connecting link RCL | 4 x clevis sling hook RCB | AISI 316 TAG

Marking: CE-marked

Safety factor: 4

Grade: 6

Part code	Diameter mm	WLL ton	WLL 45-60° t	Length	Model	Weight kg	Delivery time
R2689406-1	6	1.89	1,350	1	1.89T-6MM-RCMC-RCB-1M	4.84	3
R2689406-1.5	6	1.89	1,350	1.5	1.89T-6MM-RCMC-RCB-1.5M	6	3
R2689406-2	6	1.89	1,350	2	1.89T-6MM-RCMC-RCB-2M	7.16	3
R2689407-1	7	2.625	1,875	1	2.625T-7MM-RCMC-RCB-1M	9.37	3
R2689407-1.5	7	2.625	1,875	1.5	2.625T-7MM-RCMC-RCB-1.5M	11.59	3
R2689407-2	7	2.625	1,875	2	2.625T-7MM-RCMC-RCB-2M	13.81	3
R2689408-1	8	3.36	2,400	1	3.36T-8MM-RCMC-RCB-1M	12.44	3
R2689408-1.5	8	3.36	2,400	1.5	3.36T-8MM-RCMC-RCB-1.5M	15.8	3
R2689408-2	8	3.36	2,400	2	3.36T-8MM-RCMC-RCB-2M	19.16	3
R2689410-1	10	5.25	3,750	1	3.5T-10MM-RCMC-RCB-1M	25.52	3
R2689410-1.5	10	5.25	3,750	1.5	3.5T-10MM-RCMC-RCB-1.5M	33.06	3
R2689410-2	10	5.25	3,750	2	3.5T-10MM-RCMC-RCB-1M	40.6	3
R2689413-1	13	8.925	6,375	1	5.95T-13MM-RCMC-RCA-1M	43.61	3
R2689413-1.5	13	8.925	6,375	1.5	5.95T-13MM-RCMC-RCA-1.5M	54.85	3
R2689413-2	13	8.925	6,375	2	5.95T-13MM-RCMC-RCA-2M	66.09	3