Lifting Solutions Group
Axel Johnson International

# pewag winner pro load capacities

**Product information**

The load capacities listed are maximum values of the various sling types, stated according to the standard (Uniform Load) method of rating. ... *Read more*

**Grade:** 12

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

# pewag winner pro load capacities

| Safety factor 4 | | 1-leg chains | | 2-leg chains | | | | 3- and 4 leg chains | | 3- and 4 leg chains with load distributor | | Endless chain sling | Single lifting sling | | Double lifting sling | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | |  |  |  | |  | |  |  |  | |  |  | |  | |
| | | - | - | 0°-45° | 45°-60° | 0°-45° | 45°-60° | 0°-45° | 45°-60° | 0°-45° | 45°-60° | - | 0°-45° | 45°-60° | 0°-45° | 45°-60° |
| Load factor | | 1 | 0,8 | 1,4 | 1 | 1,12 | 0,8 | 2,1 | 1,5 | 2,8 | 2 | 1,8 | 1,4 | 1 | 2,1 | 1,5 |
| Code | d | load capacity tons | | | | | | | | | | | | | | |
| WINPRO 7 | 7 | 2,36 | 1,9 | 3,35 | 2,36 | 2,65 | 1,9 | 5 | 3,55 | 6,7 | 4,75 | 3,75 | 3,35 | 2,36 | 5 | 3,55 |
| WIN 7 | 7 | 1,9 | 1,5 | 2,65 | 1,9 | 2,12 | 1,5 | 4 | 2,8 | 5,3 | 3,75 | 3 | 2,65 | 1,9 | 4 | 2,8 |
| Ni 7 G8 | 7 | 1,5 | 1,2 | 2,12 | 1,5 | 1,7 | 1,2 | 3,15 | 2,24 | 4 | 3 | 2,5 | 2,12 | 1,5 | 3,15 | 2,24 |
| WINPRO 8 | 8 | 3 | 2,36 | 4,25 | 3 | 3,35 | 2,36 | 6,3 | 4,5 | 8,5 | 6 | 4,75 | 4,25 | 3 | 6,3 | 4,5 |
| WIN 8 | 8 | 2,5 | 2 | 3,55 | 2,5 | 2,8 | 2 | 5,3 | 3,75 | 7,1 | 5 | 4 | 3,55 | 2,5 | 5,3 | 3,75 |
| Ni 8 G8 | 8 | 2 | 1,6 | 2,8 | 2 | 2,24 | 1,6 | 4,25 | 3 | 5,6 | 4 | 3,15 | 2,8 | 2 | 4,25 | 3 |
| WINPRO 10 | 10 | 5 | 4 | 7,1 | 5 | 5,6 | 4 | 10,6 | 7,5 | 14 | 10 | 8 | 7,1 | 5 | 10,6 | 7,5 |
| WIN 10 | 10 | 4 | 3,150 | 5,6 | 4 | 4,25 | 3,15 | 8 | 6 | 11,2 | 8 | 6,3 | 5,6 | 4 | 8 | 6 |
| Ni 10 G8 | 10 | 3,15 | 2,5 | 4,25 | 3,15 | 3,5 | 2,5 | 6,7 | 4,75 | 8,5 | 6,3 | 5 | 4,25 | 3,15 | 6,7 | 4,75 |

© November 2026 - All Rights Reserved

# pewag winner pro load capacities

| | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| WINPRO 13 | 13 | 8 | 6,3 | 11,2 | 8 | 9 | 6,3 | 17 | 11,8 | - | - | 12,5 | 11,2 | 8 | 17 | 11,8 |
| WIN 13 | 13 | 6,7 | 5,3 | 9,5 | 6,7 | 7,5 | 5,3 | 14 | 10 | - | - | 10,6 | 9,5 | 6,7 | 14 | 10 |
| Ni 13 G8 | 13 | 5,3 | 4,25 | 7,5 | 5,3 | 5,9 | 4,25 | 11,2 | 8 | - | - | 8,5 | 7,5 | 5,3 | 11,2 | 8 |
| WINPRO 16 | 16 | 12,5 | 10 | 17,5 | 12,5 | 14 | 10 | 26,5 | 19 | | | 20 | 17,5 | 12,5 | 26,5 | 19 |
| WIN 16 | 16 | 10 | 8 | 14 | 10 | 11,2 | 8 | 21,2 | 15 | | | 16 | 14 | 10 | 21,2 | 15 |
| Ni 16 G8 | 16 | 8 | 6,3 | 11,2 | 8 | 9 | 6,3 | 17 | 11,8 | | | 12,5 | 11,2 | 8 | 17 | 11,8 |

© November 2026 - All Rights Reserved