



Master Link Pewag MWP

Product information

Enlarged master link with extra-large inner width compared to the AWP master link.

Material: Alloy steel

Marking: According to standard, CE-marked, Pewag or PW, winner pro or 12, H16, batch code and type.

Temperature range: -60°C up to +300°C.

Finish: Light blue powdercoated.

Standard: EN 1677-4

Warning: Not to be heat-treated.

Safety factor: 4:1

Grade: 12

| Part code | Code | WLL ton | Usable up to sling hooks following DIN 15401 No. | d mm | s mm | t mm | w mm | Weight kg | Delivery time |
|--------------|--------|---------|--|------|------|------|------|-----------|---------------|
| 403100240010 | MWP 13 | 2.36 | 4 | 14 | 10 | 120 | 70 | 0.46 | 20 |
| 403100320010 | MWP 16 | 3.2 | 5 | 17 | 13 | 140 | 80 | 0.74 | 20 |
| 403100500010 | MWP 18 | 5 | 6 | 19 | 14 | 160 | 95 | 1.05 | 20 |
| 403101010010 | MWP 26 | 10.1 | 10 | 27 | 20 | 190 | 110 | 2.47 | 20 |
| 403101750010 | MWP 36 | 17.5 | 10 | 38 | 29 | 275 | 150 | 7.48 | 20 |

Blueprint

