

## Transition Link Pewag BWI Stainless

### Product information



Stainless steel master link for 1- and 2-leg chainslings.

A higher resistance to acids and caustics compared to the standard transition links G8, G10 and G12 is just one of the many benefits that make this stamped transition link truly remarkable. The use of high-grade stainless steel also ensures that this electrically welded transition and securing link will never rust.

The transition link is part of welded assemblies, may also be used as an end link and is tested at 100 % of its maximum load capacity. Its dimensions are similar to DIN 5688-1.

The outstanding quality of this transition link is also reflected in its wide range of possible applications: It may be used as a connecting link for assembling I- to IV-leg assemblies in welded systems as well as an end link. In addition, it is ideally suited for use in water and wastewater applications and can also be used in connection with chemicals and food products; however, restrictions will apply.

... [Read more](#)

**Material:** 1.4404 (AISI 316L), 1.4462 (AISI 318LN).

**Marking:** CE-marked


**Finish:** Pickled and blasted.

**Safety factor:** 4:1

**Grade:** 6

## Transition Link Pewag BWI Stainless

### Blueprint



### Technical data

Part code	Code	WLL ton	WLL 0-45° ton	1-leg	2-leg	d mm	t mm	w mm mm	s mm	Weight kg
400100090160	BWI 7-6	0.9	0.9	5/6	5/6	7	36	16	-	0.04
400100130160	BWI 9-6	1.25	1.25	7	7	9	44	20	-	0.07
400100160160	BWI 10-6	1.6	1.6	8	8	10	44	20	-	0.09
400100250160	BWI 13-6	2.5	2.5	10	10	13	54	25	10	0.18
400100430160	BWI 16-6	4.25	4.25	13	13	16	70	34	14	0.35
400100630160	BWI 20-6	6.3	6.3	16	16	20	85	40	16	0.67
400101010160	BWI 26-6	10.07	10.07	-	-	27	140	65	20	1.92