

Fast Connector Socket FCS - with bolt



Product information

Forged clevis fittings with bolt, nut and cutterpin for fast connection of steel wire rope. Connector shall be used with non-rotating or cat 1. rotation resistant wire rope only.

The connector has to be moulded/casted on the steel wire rope with wirelock resin.

Features: Designed for use with mobile cranes.

Material: Quenched and tempered cast steel.

Finish: Blue painted or hot dip galvanized.

Warning: Compare the spelter's and the wire rope's minimum breaking load.

Part code	Code	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	Ø H mm	Ø P mm	T mm	W mm	D mm	Ø D mm	Ø J mm	K mm	TB mm	TL mm	Weight kg	Delivery time
122101300155	FCS 701 B	11-13	20	Painted	62	61	27	15	25	12	25	50	33	49	46	80	150	1.6	30
122101300152	FCS 701 B.G	11-13	20	Galvanized	62	61	27	15	25	12	25	50	33	49	46	80	150	1.6	30
122101600155	FCS 702 B	13-16	25	Painted	72	78	32	18	30	14	32	58	38	60	59	96	182	2.6	30
122101600152	FCS 702 B.G	13-16	25	Galvanized	72	78	32	18	30	14	32	58	38	60	59	96	182	2.6	30
122101900155	FCS 703 B	16-19	40	Painted	85	93	40	21	35	16	38	70	45	70	69	107	218	4.5	30
122101900152	FCS 703 B.G	16-19	40	Galvanized	85	93	40	21	35	16	38	70	45	70	69	107	218	4.5	30
122102200155	FCS 704 B	20-22	55	Painted	102	106	45	24	41	19	44	80	50	82	81	123	253	6.5	30
122102200152	FCS 704 B.G	20-22	55	Galvanized	102	106	45	24	41	19	44	80	50	82	81	123	253	6.5	30
122102600155	FCS 705 B	23-26	75	Painted	115	123	60	28	51	22	51	104	60	95	90	141	298	11	30
122102600152	FCS 705 B.G	23-26	75	Galvanized	115	123	60	28	51	22	51	104	60	95	90	141	298	11	30
122102900155	FCS 706 B	27-29	90	Painted	140	152	65	32	57	25	57	114	70	107	116	160	357	16	30
122102900152	FCS 706 B.G	27-29	90	Galvanized	140	152	65	32	57	25	57	114	70	107	116	160	357	16	30
122103200152	FCS 707 B.SR	30-32	125	Galvanized	160	171	73	39	64	28	69	126	85	125	130	185	404	18	30
122103600152	FCS 708 B.SR	33-36	125	Galvanized	160	171	73	39	64	28	69	126	85	125	130	185	404	23	30
122103900152	FCS 709 B.SR	37-39	150	Galvanized	176	187	80	42	70	30	76	142	90	136	142	201	443	29	30
122104200152	FCS 710 B.SR	40-42	170	Galvanized	188	198	88	45	76	33	76	156	95	142	150	209	474	36	30
122104800152	FCS 711 B.SR	43-48	225	Galvanized	210	232	100	52	89	39	89	176	110	167	175	237	542	58	30

Blueprint

