

Super Reeve Connector Socket SCS - with bolt



Product information

A revolutionary evolution of the Fast Connector Socket. This socket line has the smallest connector diameter available in the market today, and still meets the respective EN standards. It has been designed to go through the smallest spaces in a crane reeving system.

This unique patent pending design allows refitting by pouring in the field, saving valuable down time compared to swaging techniques.

The standard finish of our sockets is blue. Hot dipped galvanized is also available.

Material: Quenched and tempered cast steel.

Part code	Code	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	Ø H mm	Ø P mm	T mm	W mm	D mm	Ø D mm	Ø J mm	L mm	TL mm	TB mm	Weight kg	Delivery time
122101600192	SCS 902 B.GAL	13-16	25	Galvanized	85	133	32	19	30	14	32	58	32	56	98	250	96	3.1	30
122101900192	SCS 903 B.GAL	16-19	40	Galvanized	90	160	40	22	35	16	38	70	40	65	114	290	107	4.8	30
122102200192	SCS 904 B.GAL	20-22	55	Galvanized	107	184	45	26	41	19	44	80	44	77	130	336	123	8	30
122102600192	SCS 905 B.GAL	23-26	75	Galvanized	115	211	60	31	50	22	51	104	52	88	142	386	141	12	30
122102900192	SCS 906 B.GAL	27-29	90	Galvanized	140	215	65	34	57	25	57	114	58	96	159	420	160	16	14
122103200192	SCS 907 B.GAL	30-32	125	Galvanized	150	260	73	36	63	28	63	126	64	110	177	483	165	23	30
122103600192	SCS 908 B.GAL	33-36	125	Galvanized	170	260	73	40	64	28	69	126	68	114	197	503	185	25	30

Blueprint

